

KERN FH 500 EXT

Universal digital force gauge for tensile and compressive force measurements with external load cell



Article codes, product groups & Status information

Model article-code	FH 500 EXT
Model-Serie	FH-S-EXT
Assortment	Sauter
Product Type	Force measurement
Product group	Digital force-measuring devices (external sensor)
Product usage type	Main article
EAN code (Model)	4045761368606
Predecessor Model	FH 500 EXT-2.019a; FH 500 EXT-2.024a
Planned start date	2024-2HJ
Customs tariff number	90248000
CE Label	Yes

Technical data - Primary

Max. Force	500 N
Readability	0,1 N

Technical data - Construction

Dimension housing (W×D×H)	240×70×40 mm
Material housing	Plastic
Mounting thread	External thread M6

Technical data - Display

Display type	LCD
Display reverse	Yes

Technical data - Power supply

Power supply	Battery & Power supply
Battery type	NiMH
Operating time (Display off)	40 h
Operating time (Display on)	24 h
Interfaces	RS-232 standard;USB-Device

Technical data - Measuring system

Units	N
Tolerance (% from Max.)	0,5%
Force direction	Compression;tension

Technical data - Functions

Statistic-Function	Yes
Peak-Function	Yes
Limit value (Min - Max)	Yes
Audible ready signal	Yes
Interface	RS-232 standard;USB-Device

Technical data - Environmental conditions

Maximum operating temperature	40 °C
Minimum storage temperature	40 °C

Technical data - Packing & Shipping

Dimensions packaging (W×D×H)	330×190×175 mm
Gross weight	2,2 kg

KERN FH 500 EXT

Universal digital force gauge for tensile and compressive force measurements with external load cell



Net weight	0,90 kg
Shipping method	Parcel service
UN number	Ni-MH (UN 3496, Packing Instruction #0, Not Restricted as per Special Provision A199)
Packaging component - by weight - cardboard	210 g
Packaging component - by weight - plastics	14 g
Packaging component - by weight - styrofoam	639,5 g
Delivery time	1 d

Technical data - Counting data

Memory	Yes
Value memory - number of groups	1
Value memory - number of cells (per group)	10

Optional Services

DAkkS calibration - push/pull	963-361
DAkkS calibration - push only	963-261
DAkkS calibration - pull only	963-161

Functions

Standard



Option

