

PRODUCT BROCHURE

SAUTER FH 500 EXT

Date: 22.09.2025

ENGLISH



Universal digital force gauge for tensile and compressive force measurements with external load cell

CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

Phone : +49 7433 9933-0
Fax : +49 7433 9933-149
Email : info@kern-sohn.com
Web : www.kern-sohn.com



Scan here for more
information

PRODUCT SHOWCASE



DESCRIPTION

- Turnable display with backlight
- NEW: USB interface for data transfer and power supply as standard
- Data interface RS-232 as standard
- Selectable measuring units: N, kN, kgf, tf
- Peak-Hold function to capture the peak value or Track function for continuous display of measurement
- Measuring with tolerance range (limit-setting function): Upper and lower limit adjustable, in pull and push direction. The process is supported by an audible and visual signal
- Auto-Power-Off
- Internal memory for up to 10 measurement values
- Mini Statistics Kit: calculates the average result from up to 10 stored measured values, as well as min., max., n
- Tension loops and compression plates are included in delivery
- Delivered in a robust carrying case

SPECIFICATIONS

Article codes, product groups & Status information

Model article-code	FH 500 EXT
Model-Serie	FH-S-EXT
Assortment	Sauter

Product Type	Force measurement
Product group	Digital force-measuring devices (external sensor)
Product usage type	Main article
EAN code (Model)	404576 1368606

Predecessor Model FH 500 EXT-2019a; FH 500 EXT-2024a

Customs tariff number 90248000

CE Label yes

Technical data - Primary

Max. Force 500 N

Readability 0.1 N

Technical data - Construction

Dimension housing (W×D×H) 240×70×40 mm

Material housing plastic

Mounting thread External thread M6

Technical data - Display

Display type LCD

Display reverse yes

Technical data - Power supply

Power supply Battery & Power supply

Battery type NiMH

Operating time (Display off) 40 h

Operating time (Display on) 24 h

Technical data - Measuring system

Units N

Tolerance (% from Max.) 0.5%

Force direction compression;tension

Technical data - Functions

Statistic-Function yes

Peak-Function yes

Limit value (Min - Max) yes

Audible ready signal yes

Interface RS-232 standard;USB-Device

Technical data - Environmental conditions

Maximum operating temperature 40 °C

Minimum storage temperature 40 °C

Technical data - Packing & Shipping

Dimensions packaging (W×D×H) 330×190×175 mm

Gross weight 2.2 kg

Net weight 0.90 kg

Shipping method Parcel service

UN number Ni-MH (UN 3496, Packing Instruction #0, Not Restricted as per Special Provision A199)

Packaging component - by weight - cardboard 210 g

Packaging component - by weight - plastics 14 g

Packaging component - by weight - styrofoam 639.5 g

Delivery time 1 d

Technical data - Counting data

Memory	yes
Value memory - number of groups	1
Value memory - number of cells (per group)	10

Optional Services

DAkkS calibration - push/pull	963-361
DAkkS calibration - push only	963-261
DAkkS calibration - pull only	963-161

FUNCTIONS

Standard



PEAK



PUSH/PULL



MEMORY



RS 232



USB



STATISTIC



TOL



ZERO



ACCU



ACCU



230 V



230 V



1 DAY



1 DAY

Option



SOFTWARE



+4 DAYS



+4 DAYS

ACCESSORIES

Model	Description
YKA-01	Power supply KERN YKA-01
AC 01	Screw Tension Clamp SAUTER AC 01
AC 02	Stainless steel ball-shaped head SAUTER AC 02
AC 03	Clamp SAUTER AC 03
AC 12	Clamp SAUTER AC 12
AC 14	Screw Tension Clamp SAUTER AC 14
AC 22	Fine point clamp SAUTER AC 22

Model	Description
AC 18	Clamp SAUTER AC 18
YKA-02	Power supply adapter set KERN YKA-02
AC 43	Standard attachments SAUTER AC 43
AC 01R	Screw Tension Clamp SAUTER AC 01R
AC 03R	Clamp SAUTER AC 03R
AC 11R	Clamp SAUTER AC 11R
AC 12R	Clamp SAUTER AC 12R
AC 14R	Screw Tension Clamp SAUTER AC 14R
AC 18R	Clamp SAUTER AC 18R
AC 22R	Fine point clamp SAUTER AC 22R
AE 500	Screw Tension Clamp SAUTER AE 500
AFM 05	Adapter KERN AFM 05
AFM 06	Adapter KERN AFM 06
AFM 07	Sleeve SAUTER AFM 07
AFM 12	Adapter SAUTER AFM 12
AFM 15	Sleeve SAUTER AFM 15
FS-E07	Power supply KERN FS-E07
AE 01	Standard Clamp AE 01
AE 02	Standard Clamp AE 02
AE 03	Clamp SAUTER AE 03
AE 04	Clamp SAUTER AE 04
AE 05	Rope and thread tension clamp SAUTER AE 05
AE 06	Clamp SAUTER AE 06
AE 07	Wedge Clamp with jaws AE 07
AC 45	Force sensor SAUTER AC 45
AC 46	Force sensor SAUTER AC 46
AC 47	Force sensor SAUTER AC 47
AE 08	Pressure plate SAUTER AE 08
FH-A04	Interface cable FH-A04

SERVICES

Model	Description
963-161	DAkkS Calibration KERN 963-161
961-161	Factory calibration KERN 961-161
961-261	Factory calibration KERN 961-261
961-361	Factory calibration KERN 961-361
963-261	DAkkS Calibration KERN 963-261
963-361	DAkkS Calibration KERN 963-361
970-105	Warranty extension KERN (+2 years) 970-105

SPARE PARTS

Model	Description
YKA-02	Power supply adapter set KERN YKA-02
FH-A02	Display overlay FH-A02
OBB-A1569	UK power supply unit KERN OBB-A1569
FS-E06	Cable SAUTER FS-E06
FS-E07	Power supply KERN FS-E07

SOFTWARES

Model	Description
AFH LD	Data Transfer Software SAUTER AFH LD
AFH FAST	Data Transfer Software SAUTER AFH FAST

RELATED ARTICLES DATA

Model name	Max. Force	Readability
FH 100 EXT	100 N	0.05 N
FH 200 EXT	200 N	0.1 N
FH 500 EXT	500 N	0.1 N
FH 50 EXT	50 N	0.01 N