PRODUCT BROCHURE

KERN
YKI-02

RS-232 / Bluetooth adapter

CONTACT

KERN & SOHN GmbH

Ziegelei 1

72336 Balingen

Germany

Phone : +49 7433 9933-0

Fax : +49 7433 9933-149

Email : info@kern-sohn.com

Web : www.kern-sohn.com

PRODUCT SHOWCASE

DESCRIPTION

- Adapter for the wireless connection of balances, force measuring devices etc. with an RS-232 interface to Bluetooth devices, such as Bluetooth printers, tablets, laptops, Smartphones etc

- In this way, where there is a physical separation or a large distance between the devices, the weighing data from one or several balances can be easily sent without cable and printed on a WiFi printer or transferred to a WiFi device (you would need the relevant software on the WiFi device, not included with the delivery)

- The compact adapter with its attractive design can usually be connected directly to the balance, e.g. an additional interface cable would not be necessary.

- Bluetooth adapter will be powered by the balance (if compatible) or with the mains adapter which is supplied as standard

- Range up to 100 m in the open, depending on obstacles, such as, for example, walls, and the sensitivity and type of antenna of the receiver

- Intersections of sending and receiving lines using the DCE/DTE switch

- Compatible with KERN BalanceConnection software

- Scope of delivery: RS-232/Bluetooth adapter, mains adapter (EU/UK/US/AUS/CH), USB-A to Mini USB B cable, gender changer, driver CD.

SPECIFICATIONS

Article codes, product groups & Status information

Model article-code	YKI-02
Model-Serie	YKI

Assortment	KERN
Product Type	Laboratory balances
Product group	Accessories (printer, etc.)
Product usage type	Accessories/DL

KERN®

EAN code (Model)	4045761161573
Customs tariff number	84239010
CE Label	yes

Technical data - Power supply

Mains adapter/adapter included	CH;EURO

Technical data - Packing & Shipping

Dimensions packaging (W×D×H)	160×155×65 mm
Gross weight	0.30 kg
Net weight	0.10 kg
Shipping method	Parcel service
Packaging component - by weight - cardboard	190 g
Delivery time	1 d

FUNCTIONS

Standard

RS 232	BT

ENGLISH