KERN SFB 20K2HIP

Stainless steel platform scale with IP65/IP67 protection and elevated display



Article codes, product groups & Status information	
Model article-code	SFB 20K2HIP
Model-Serie	SFB
Assortment	Scales
Product Type	Industrial balance
Product group	Platform scales
Product usage type	Main article
EAN code (Model)	4045761247857
Predecessor Model	SFB 20K2HIP-2.017a; SFB 20K2HIP-2.020a
Planned start date	2021-2HJ
Customs tariff number	84238129
CE Label	Yes
Country of Origin	CN

Technical data - Primary	
Weighing capacity	20 kg
Readability	0,002 kg
Net weight	7,5 kg
Platform size	300×240 mm
Indicator cable length	0 m
Dimension weighing platform (W×D×H)	300×240×107 mm

Technical data - Construction	
Dimensions display casing (W×D×H)	266×165×96 mm
Material weighing plate	Stainless steel
Material Platform construction	Stainless steel
Bubble Level	Yes
Revolving screw feet	Yes
Weighing surface (d)	300×240 mm
Dimensions of weighing plate (W×D)	300×240 mm
Indicator cable length	3 m
Wall mount	Yes
IP protection indicator	IP65
IP protection platform	No IP protection
IP protection load cell	IP67

Technical data - Display	
Display height	52 mm
Backlight	Yes

Technical data - Power supply	
Mains adapter/adapter included	CH;EURO;UK;US
Charging time	12 h
Input Voltage	110 V - 230 V AC
Operating time (Backlight off)	35 h
Interfaces	Analog (0 - 10 V) (optional, factory);Analog (4 - 20 mA) (optional, factory);Bluetooth BTC (v2.0) (optional, factory);RS-232 (optional, factory)

KERN SFB 20K2HIP

Stainless steel platform scale with IP65/IP67 protection and elevated display

Technical data - Measuring system	
Calibration method	Adjusting with external weight
Linearity	± 0,002 kg
Readability	0,002 kg
Recommended adjusting weight	20 kg (M1)
Repeatability	0,002 kg
Resolution	10.000
Stabilisation time under laboratory conditions	2 s
Tare range	-20 kg
Warm up time	30 min
Weighing system	Strain gauge
Weighing units	G;Hj, tJ;kg;lb;lb:oz
load cell connection	6-Leiter

Technical data - Environmental conditions	
Maximum humidity	95 %
Maximum operating temperature	40 °C
Minimum ambient temperature	-10 °C
Minimum humidity	10 %

Technical data - Packing & Shipping	
Dimensions packaging (W×D×H)	695×415×225 mm
Gross weight	10 kg
Net weight	8 kg
Shipping method	Parcel service
UN number	2800
Packaging component - by weight - cardboard	1.140 g
Packaging component - by weight - styrofoam	1.140 g
Delivery time	1 d

Optional Services	
DAkkS Calibration	963-128

Functions

Standard



Option



Factory


RS 232