

PRODUCT BROCHURE

KERN KFP 1500V40SM

Date: 11.03.2026

ENGLISH



Platform: entirely out of stainless steel

CONTACT


KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

Phone : +49 7433 9933-0
Fax : +49 7433 9933-149
Email : info@kern-sohn.com
Web : www.kern-sohn.com



Scan here for more
information

PRODUCT SHOWCASE



DESCRIPTION

- Weighing bridge entirely made of stainless steel, extremely resistant to bending because of its high material thickness
- Weighing plate fixed with stainless steel screws, for easier access to the loadcells from above
- 4 stainless steel load cells with protection against dust and water splashes to IP68
- OIML R60 approval for verification, Class III, 3000 e
- Can be built in using pit frames (optional)
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard
- Comfortable levelling of the weighing bridge from the top

SPECIFICATIONS

Article codes, product groups & Status information

Model article-code	KFP 1500V40SM
Model-Serie	KFP
Assortment	KERN
Product Type	Industrial balance
Product group	Platforms
Product usage type	Spare part;Main article

EAN code (Model)	4045761493896
Predecessor Model	KFP 1500V40SM-2024a
Customs tariff number	90318080
Country of Origin	CN

Technical data - Primary

Weighing capacity	1500 kg
Readability	500 g
Verification value (e)	500 g

Minimum load (Min)	10 kg
Net weight	95 kg
Dimension weighing platform (W×D×H)	1000×1000×85 mm

Verification by KERN possible	yes
-------------------------------	-----

Technical data - Construction

Material weighing plate	stainless steel
Revolving screw feet	yes
Weighing surface (d)	1000×1000 mm
Dimensions of weighing plate (W×D)	1000×1000 mm
IP protection platform	IP67
IP protection load cell	IP68

FUNCTIONS

Standard



Factory



ENGLISH

Technical data - Measuring system

load cell connection	6-Leiter
----------------------	----------

Technical data - Packing & Shipping

Dimensions packaging (W×D×H)	1115×1080×350 mm
Gross weight	135 kg
Net weight	95 kg
Shipping method	Freight
Packaging component - by weight - cardboard	720 g
Packaging component - by weight - wood	35280 g
Delivery time	2 d

Technical data - Verification

ACCESSORIES

Model	Description
BFN-A03	Pair of base plates KERN BFN-A03
BFN-A05	Ramp KERN BFN-A05
BFN-A06	Pit frame KERN BFN-A06

SERVICES

Model	Description
965-230	Verification / Conformity assessment according to NAWI (2014/31/EU) KERN 965-230
965-232	Verification / Conformity assessment according to NAWI (2014/31/EU) KERN 965-232
965-413	Assembly of components (> 350 kg - 1500 kg) 965-413
963-130	DAkkS Calibration KERN 963-130
970-111	Warranty extension KERN (+2 years) 970-111

SPARE PARTS

Model	Description
RNFN-1002	Load cell KERN RNFN-1002
RKFPV20-8002	Level bubble RKFPV20-8002
RKFP-5003	Cable RKFP-5003
RKFP-1007	Load cell KERN RKFP-1007
RKFP-8005	Adjustable base foot RKFP-8005
RNFN-1003	Load cell KERN RNFN-1003

RELATED ARTICLES DATA

Model name	Weighing capacity	Readability	Verification value (e)	Minimum load (Min)	Net weight	Dimension weighing platform (W×D×H)
KFP 150V30LM	150 kg	5 g	50 g	1 kg	24.3 kg	650×500×136 mm
KFP 60V30LM	60 kg	2 g	20 g	400 g	13.3 kg	500×400×117 mm
KFP 60V30XLM	60 kg	2 g	20 g	400 g	22 kg	650×500×136 mm

Model name	Weighing capacity	Readability	Verification value (e)	Minimum load (Min)	Net weight	Dimension weighing platform (W×D×H)
<u>KFP 150V20LM</u>	60 kg; 150 kg	5 g	20 g; 50 g	400 g; 1 kg	18.8 kg	650×500×139 mm
<u>KFP 150V20M</u>	60 kg; 150 kg	5 g	20 g; 50 g	400 g; 1 kg	6.58 kg	500×400×127 mm
<u>KFP 150V30LM-2022e</u>	150 kg	10 g	50 g	1 kg	20.5 kg	650×500×139 mm
<u>KFP 150V30M</u>	150 kg	10 g	50 g	1 kg	9.8 kg	500×400×120 mm
<u>KFP 150V30SM</u>	150 kg	10 g	50 g	1 kg	9.35 kg	400×300×111 mm
<u>KFP 15V20LM</u>	6 kg; 15 kg	500 mg	2 g; 5 g	40 g; 100 g	6.3 kg	400×300×117 mm
<u>KFP 15V20M</u>	6 kg; 15 kg	500 mg	2 g; 5 g	40 g; 100 g	3.8 kg	300×240×109 mm
<u>KFP 15V30M</u>	15 kg	1 g	5 g	100 g	7.9 kg	300×240×107 mm
<u>KFP 300V20M</u>	150 kg; 300 kg	10 g	50 g; 100 g	1 kg; 2 kg	18.8 kg	650×500×139 mm
<u>KFP 300V30M</u>	300 kg	20 g	100 g	2 kg	20.5 kg	650×500×139 mm
<u>KFP 30V20M</u>	15 kg; 30 kg	1 g	5 g; 10 g	20 g	6.3 kg	400×300×117 mm
<u>KFP 30V20SM</u>	15 kg; 30 kg	1 g	5 g; 10 g	100 g; 200 g	3.8 kg	300×240×109 mm
<u>KFP 30V30M</u>	30 kg	2 g	10 g	200 g	7.2 kg	400×300×111 mm
<u>KFP 30V30SM</u>	30 kg	2 g	10 g	200 g	5 kg	300×240×107 mm
<u>KFP 3V20M</u>	3 kg	100 mg	1 g	20 g	3.3 kg	230×230×106 mm
<u>KFP 600V20AM</u>	600 kg	20 g	200 g	4 kg	41.8 kg	800×600×192 mm
<u>KFP 60V20LM</u>	30 kg; 60 kg	2 g	10 g; 20 g	200 g; 400 g	9.8 kg	500×400×127 mm
<u>KFP 60V20M</u>	30 kg; 60 kg	2 g	10 g; 20 g	200 g; 400 g	6.3 kg	400×300×117 mm

ENGLISH

Model name	Weighing capacity	Readability	Verification value (e)	Minimum load (Min)	Net weight	Dimension weighing platform (W×D×H)
<u>KFP 60V30LM-2022e</u>	60 kg	5 g	20 g	400 g	9.8 kg	500×400×120 mm
<u>KFP 60V30M</u>	60 kg	5 g	20 g	400 g	7.2 kg	400×300×111 mm
<u>KFP 60V30XLM-2022e</u>	60 kg	5 g	20 g	400 g	20.5 kg	650×500×139 mm
<u>KFP 6V20LM</u>	6 kg	200 mg	1 g; 2 g	20 g; 40 g	3.8 kg	300×240×109 mm
<u>KFP 6V20M</u>	6 kg	200 mg	1 g; 2 g	20 g; 40 g	4.4 kg	230×230×106 mm
<u>KFP 6V40M</u>	6 kg	500 mg	1 g; 2 g	20 g	6.52 kg	300×240×107 mm
<u>KFP 15V40M</u>	15 kg	1 g	2 g; 5 g	40 g	4.8 kg	300×240×107 mm
<u>KFP 15V40LM</u>	15 kg	1 g	2 g; 5 g	40 g	6.1 kg	400×300×111 mm
<u>KFP 30V40M</u>	30 kg	2 g	5 g; 10 g	100 g	7.7 kg	400×300×111 mm
<u>KFP 30V40LM</u>	30 kg	2 g	5 g; 10 g	100 g	10.2 kg	500×400×120 mm
<u>KFP 60V40M</u>	60 kg	5 g	10 g; 20 g	200 g	9.1 kg	400×300×123 mm
<u>KFP 60V40LM</u>	60 kg	5 g	10 g; 20 g	200 g	10.2 kg	500×400×126 mm
<u>KFP 150V40M</u>	150 kg	10 g	20 g; 50 g	400 g	11.7 kg	500×400×126 mm
<u>KFP 150V40LM</u>	150 kg	10 g	20 g; 50 g	400 g	20 kg	650×500×139 mm
<u>KFP 300V40M</u>	300 kg	20 g	50 g; 100 g	1 kg; 2 kg	20 kg	650×500×139 mm
<u>KFP 30V20LM</u>	15 kg; 30 kg	1 g	5 g; 10 g	20 g	10.53 kg	500×400×127 mm
<u>KFP 1500V20NM</u>	1500 kg	500 g	500 g	10 kg	147 kg	1500×1250×85 mm
<u>KFP 1500V20SNM</u>	1500 kg	500 g	500 g	10 kg	96 kg	1000×1000×85 mm

Model name	Weighing capacity	Readability	Verification value (e)	Minimum load (Min)	Net weight	Dimension weighing platform (W×D×H)
<u>KFP 1500V40M</u>	1500 kg	500 g	500 g	10 kg	146 kg	1500×1250×85 mm
<u>KFP 1500V40SM</u>	1500 kg	500 g	500 g	10 kg	95 kg	1000×1000×85 mm
<u>KFP 3000V20LNM</u>	3000 kg	1 kg	1 kg	20 kg	172 kg	1500×1500×85 mm
<u>KFP 3000V20NM</u>	3000 kg	1 kg	1 kg	20 kg	147 kg	1500×1250×85 mm
<u>KFP 3000V40M</u>	3000 kg	1 kg	1 kg	20 kg	145 kg	1500×1250×85 mm
<u>KFP 6000V20M</u>	6000 kg	2 kg	2 kg	40 kg	223 kg	1500×1500×123 mm
<u>KFP 600V20NM</u>	600 kg	200 g	200 g	4 kg	147 kg	1500×1250×85 mm
<u>KFP 600V20SNM</u>	600 kg	200 g	200 g	4 kg	95 kg	1000×1000×85 mm
<u>KFP 600V40SM</u>	600 kg	200 g	200 g	4 kg	95 kg	1000×1000×85 mm