

PRODUCT BROCHURE

OPTICS ORA 4UA

Date: 30.05.2026

ENGLISH



Refractive index measurement for laboratories and the industry

CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

Phone : +49 7433 9933-0
Fax : +49 7433 9933-149
Email : info@kern-sohn.com
Web : www.kern-sohn.com



Scan here for more
information

PRODUCT SHOWCASE



DESCRIPTION

- The models in the KERN ORA-U range are universal, maintenance-free analogue manual refractometers
- The handy and robust design allows the easy, efficient and sustainable use in everyday life
- Manually calculated conversions and errors of the user are avoided by multiple selectable scales.
- These scales are especially developed, exactly calculated and checked. They are also characterized by their thin and clear lines.
- The optical system and the prism cover are made of special material which allows a low-tolerance measuring.
- NEW: With engraved serial number
- All models are fitted with an eyepiece which can be adjusted easily and smoothly to different visual capacities
- The temperature compensation ("ATC") enables accurate measurement at different ambient temperatures (10 °C to 30 °C)
- Included with the delivery:
 - Storage box
 - Calibration solution
 - Pipette
 - Screwdriver
 - Cleaning cloth
- Further accessories are available optionally.
- This model is particularly suitable for measuring and determining urea, glycol concentration, measuring the freezing point of screen wash (CW) and battery fluid (BF). Furthermore, this model is suitable for measuring temperature-exchange systems.

SPECIFICATIONS

Article codes, product groups & Status information

Model article-code	ORA 4UA
Model-Serie	ORA-U
Assortment	Optics
Product Type	Refractometers
Product group	Analogue refractometers
Product usage type	Main article
EAN code (Model)	4045761483101
Predecessor Model	ORA 4UA-2024a
Customs tariff number	90275000
Country of Origin	CN

Technical data - Primary

Scales	EG PG CW BF Urea
Scale Range	-50 °C - 0 °C -50 °C - 0 °C -40 °C - 0 °C 1,10 kg/l - 1,40 kg/l 30 % - 35 %
ATC	yes

Technical data - Construction

Type	Handheld refractometer
Display scale	Analogue
Dimensions (W×D×H)	160×40×40 mm

Technical data - Measuring system

Measuring method	Light refraction
------------------	------------------

Measuring Temp min	10 °C
Measuring Temp max	30 °C
Readout	1 °C 1 °C 5 °C 0.01 kg/l 0.2 %

Technical data - Environmental conditions

Storage Temp Min	-5 °C
Stotage Temp Max	40 °C

Technical data - Packing & Shipping

Dimensions packaging (W×D×H)	215×94×65 mm
Gross weight	0.35 kg
Net weight	0.30 kg
Shipping method	Parcel service
Packaging component - by weight - cardboard	26.14 g
Packaging component - by weight - plastics	26.14 g
Delivery time	1 d

Optional Services

ISO Calobration	961-290
-----------------	---------

FUNCTIONS

Standard



Option

ENGLISH



ACCESSORIES

Model	Description
ORA-A1101	Prism cover ORA-A1101
ORA-A2103	Leather bag ORA-A2103
ORA-A1010	Liquid KERN ORA-A1010
OCS-A1101	Cleaning liquid KERN OCS-A1101

SERVICES

Model	Description
961-290	Factory calibration KERN 961-290
961-290R	Factory calibration KERN 961-290R

SPARE PARTS

Model	Description
ORA-A1001	Liquid KERN ORA-A1001
ORA-A2001	Prismatic flap ORA-A2001
ORA-A2002	Cover ORA-A2002
ORA-A2003	Eyepiece - rubber ORA-A2003
ORA-A2004	Rubber grip (40 mm) ORA-A2004
ORA-A2101	Refractometer box ORA-A2101
ORA-A2105	Single shipping box ORA-A2105
ORA-A2010	Pipette ORA-A2010

RELATED ARTICLES DATA

Model name	Scales	Scale Range	ATC
ORA 4FB	EG PG CW BF	-50 °C - 0 °C -50 °C - 0 °C -40 °C - 0 °C 1,10 kg/l - 1,40 kg/l	-
ORA 1UB	Urea	0 % - 40 %	-

Model name	Scales	Scale Range	ATC
ORA 1UA	Urea	0 % - 40 %	yes
ORA 4FA	EG PG CW BF	-50 °C - 0 °C -50 °C - 0 °C -40 °C - 0 °C 1,10 kg/l - 1,40 kg/l	yes
ORA 4UA	EG PG CW BF Urea	-50 °C - 0 °C -50 °C - 0 °C -40 °C - 0 °C 1,10 kg/l - 1,40 kg/l 30 % - 35 %	yes