





Platform scale with integrated rechargeable battery pack, a bright LED display and a column for greatest ease of use

Features

- Weighing plate stainless steel, painted steel base
- Superior display size: digit height 52 mm, bright with high contrast for easy reading of weighing results, even in poor lighting conditions
- High mobility: thanks to rechargeable battery operation, compact, lightweight construction, it is suitable for the use in several locations (production, warehouse, dispatch department, etc.)
- Weighing with tolerance range (checkweighing): a visual and audible signal helps with portioning, dispensing or grading
- Summation of weight values
- RS-232 data interface for connection to a printer as standard

Technical data

- Large LED segments display, digit height 52 mm
- Weighing platform dimensions, stainless steel
  - A W×D×H 400×300×124 mm
  - B W×D×H 500×400×120 mm
  - C W×D×H 600×500×140 mm
- Dimensions of display device W×D×H 252×162×57 mm
- Net weight approx. 8 kg
- Permissible ambient temperature 0 °C/40 °C

STANDARD



OPTION



Model	Weighing capacity [Max]	Readability [d]	Reproducibility	Linearity	Weighing plate	Cable length	Net weight	Options
								Calibr. Certificate
KERN	kg	g	g	g		approx. m	approx. kg	DAkkS accr. KERN
EFC 30K-3	30	2	2	± 6	A	3	8	963-128
EFC 30K-3L	30	2	2	± 6	B	3	11	963-128
EFC 60K-3	60	5	5	± 15	A	3	8	963-129
EFC 60K-3L	60	5	5	± 15	B	3	11	963-129
EFC 100K-3	150	10	10	± 30	B	3	11	963-129
EFC 100K-3L	150	10	10	± 30	C	3	20	963-129
EFC 300K-2	300	20	20	± 60	C	3	20	963-129