KERN IFC 600K-2

Robust industrial scales with up to three interfaces



KERN IFC 600K-2

Robust industrial scales with up to three interfaces

Article codes, product groups & Status information	
Model article-code	IFC 600K-2
Model-Serie	IFC
Assortment	Scales
Product Type	Industrial balance
Product group	Platform scales
Product usage type	Main article
EAN code (Model)	4045761475694
Predecessor Model	IFB 600K-2; IFB 600K-2-2.024a; IOC 600K-2
Planned start date	2024-1HJ
Customs tariff number	84238220
CE Label	Yes
Country of Origin	CN

Technical data - Primary	
Weighing capacity	600 kg
Readability	0,02 kg
Minimum piece weight	200 g
Net weight	38,5 kg
Platform size	800×600 mm
Indicator cable length	3 m
Dimension weighing platform (W×D×H)	800×600×192 mm

Technical data - Construction	
Dimensions display casing (W×D×H)	220×150×66,5 mm
Material weighing plate	Stainless steel
Material Platform construction	Steel, powder-coated
Bubble Level	Yes
Revolving screw feet	Yes
Weighing surface (d)	800×600 mm
Dimensions of weighing plate (W×D)	800×600 mm
Indicator cable length	3 m
Wall mount	Yes
IP protection indicator	No IP protection
IP protection platform	No IP protection
IP protection load cell	IP65

Technical data - Display	
Display height	48 mm
Backlight	Yes

Technical data - Power supply	
Battery	3V CR2.032
Mains adapter/adapter included	CH;EURO;UK;US
Charging time	8 h
Input Voltage	100 V - 240 V, 50 / 60 Hz
Operating time (Backlight off)	48 h
Rechargeable battery	Rchrg. battery optional - intern
Interfaces	Alibi Speicher (optional, factory);Analog (0 - 10 V) (optional);Analog (4 - 20 mA) (optional);Bluetooth BLE (v4.0) (optional);Ethernet (optional);KUP;RS-232 (optional);USB-Device (optional);WLAN (optional)

KERN IFC 600K-2

Robust industrial scales with up to three interfaces

Technical data - Measuring system	
Calibration method	Adjusting with external weight
Linearity	± 0,06 kg
Readability	0,02 kg
Recommended adjusting weight	600 kg (M1)
Repeatability	0,02 kg
Resolution	30.000
Stabilisation time under laboratory conditions	3 s
Warm up time	120 min
Weighing system	Strain gauge
Weighing units	%;ffa;g;kg;lb;PCS
load cell connection	6-Leiter

Technical data - Environmental conditions	
Maximum humidity	80 %
Maximum operating temperature	40 °C
Minimum ambient temperature	-10 °C
Minimum humidity	0 %

Technical data - Packing & Shipping	
Dimensions packaging (W×D×H)	910×710×295 mm
Gross weight	42 kg
Net weight	40 kg
Shipping method	Freight
UN number	3091
Packaging component - by weight - cardboard	1,6 kg
Packaging component - by weight - styrofoam	1,6 kg
Delivery time	2 d

Technical data - Counting data	
Counting resolution	30.000
Mininum piece weight at piece counting (Laboratory)	20 g
Minimum piece weight	200 g

Optional Services	
DAkkS Calibration	963-130

Functions

Standard



Option



Factory

