
KERN UXC 1.5T-4M

Pallet scale with stainless steel load support (IP67) and stainless steel display device (IP68), verification optional



Article codes, product groups & Status information	
Model article-code	UXC 1.5T-4M
Model-Serie	UXC
Assortment	Scales
Product Type	Industrial balance
Product group	Pallet scales
Product usage type	Main article
EAN code (Model)	4045761481565
Predecessor Model	UFN 15T5IPM
Planned start date	2025-1HJ
Customs tariff number	84238220
CE Label	Yes
Country of Origin	CN

Technical data - Primary	
Weighing capacity	1.500 kg
Readability	0,5 kg
Minimum load (Min)	10 kg
Net weight	53 kg

Technical data - Construction	
Dimensions display casing (W×D×H)	232×150×77,3 mm
Material weighing plate	Stainless steel
Bubble Level	Yes
Revolving screw feet	Yes
Weighing surface (d)	1.190×840 mm
Dimensions of weighing plate (W×D)	1.190×840 mm
Indicator cable length	5 m
Wall mount	Yes
Dimension weighing platform (W×D×H)	1.361×840×80 mm
IP protection indicator	IP68
IP protection platform	IP67
IP protection load cell	IP67

Technical data - Display	
Display height	48 mm
Backlight	Yes

Technical data - Power supply	
Battery	no battery
Mains adapter/adapter included	EURO
Charging time	8 h
Input Voltage	110 V - 240 V AC
Operating time (Backlight off)	22 h
Rechargeable battery	Rchrg. battery optional - intern
Interfaces	Alibi Speicher (optional, factory);Analog (0 - 10 V) (optional, factory);Analog (4 - 20 mA) (optional, factory);Bluetooth BLE (v4.0) (optional, factory);Ethernet (optional, factory);RS-232 (optional, factory);USB-Device (optional, factory);WLAN (optional, factory)

KERN UXC 1.5T-4M

Pallet scale with stainless steel load support (IP67) and stainless steel display device (IP68), verification optional

Technical data - Measuring system	
Calibration method	Adjusting with external weight
Linearity	± 0,5 kg
Readability	0,5 kg
Recommended adjusting weight	1.500 kg (M1)
Repeatability	0,5 kg
Resolution	3.000
Warm up time	10 min
Weighing units	%;ffa;g;kg;PCS
Linearity (in dots)	2
load cell connection	6-Leiter

Technical data - Environmental conditions	
Maximum humidity	80 %
Maximum operating temperature	40 °C
Minimum ambient temperature	-10 °C
Minimum humidity	0 %

Technical data - Packing & Shipping	
Dimensions packaging (W×D×H)	1.405×890×315 mm
Gross weight	90 kg
Net weight	55 kg
Shipping method	Freight
Packaging component - by weight - cardboard	700 g
Packaging component - by weight - wood	34,3 kg

Delivery time	3 d

Optional Services	
DAkkS Calibration	963-130
Verification	965-230

Technical data - Counting data	
Counting resolution	3.000
Mininum piece weight at piece counting (Laboratory)	500 g
Minimum piece weight	5 kg

Technical data - Verification	
Verification value (e)	0,5 kg
Minimum Load Min	10 kg
Verification by KERN possible	Yes
Verification class	III

Functions

Standard



Option



Factory

