

PRODUCT BROCHURE

KERN KFP 150V40LM

Date: 29.04.2025

ENGLISH



Platform: entirely out of stainless steel

CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

Phone : +49 7433 9933-0
Fax : +49 7433 9933-149
Email : info@kern-sohn.com
Web : www.kern-sohn.com



Scan here for more
information

DESCRIPTION

- Platform: entirely out of stainless steel
- 1 load cell, stainless steel, encapsulated, IP68, OIML R60 approval for verification, class III, 3000 e
- Level indicator and levelling feet for accurate levelling of the balance

SPECIFICATIONS

Article codes, product groups & Status information

Model article-code	KFP 150V40LM
Model-Serie	KFP
Assortment	KERN
Product Type	Industrial scales
Product group	Platforms
Product usage type	Spare part;Main article
EAN code (Model)	404576 1475892
Customs tariff number	90318080

Technical data - Primary

Weighing capacity	150 kg
Readability	10 g
Verification value (e)	20 g; 50 g
Minimum load (Min)	400 g
Net weight	20 kg
Dimension weighing platform (W×D×H)	650×500×139 mm

Technical data - Construction

Material weighing plate	stainless steel
Revolving screw feet	yes
Weighing surface (d)	650×500 mm

Dimensions of weighing plate (W×D) 650×500 mm

Dimensions weighing platform 650×500×139 mm

IP protection platform no IP protection

IP protection load cell IP68, IP69K

Technical data - Measuring system

Readability 10 g
load cell connection 6-Leiter

Technical data - Packing & Shipping

Dimensions packaging (W×D×H) 1050×675×250 mm

Gross weight 24 kg

Net weight 20 kg

Shipping method Parcel service

Packaging component - by weight - cardboard 2 kg

Packaging component - by weight - plastics 2 kg

Delivery time 1 d

Technical data - Verification

Verification Value E 20 g; 50 g

Minimum Load Min 400 g

Verification by KERN possible yes

FUNCTIONS

Standard



Factory



SERVICES

Model	Description
965-229	Verification / Conformity assessment according to NAWI (2014/31/EU) KERN 965-229
965-412	Assembly of components (> 50 kg - 350 kg) 965-412
963-129	DAkkS Calibration KERN 963-129
970-107	Warranty extension KERN (+2 years) 970-107

SPARE PARTS

Model	Description
RKFPV20-6005	Weighing plate KERN RKFPV20-6005
RKFPV30-1001	Load cell KERN RKFPV30-1001
RKFP-8001	Adjustable base foot RKFP-8001
RKFP-8008	Rubber shock absorber RKFP-8008
RKFP-8009	Rubber shock absorber RKFP-8009

RELATED ARTICLES DATA

Model name	Weighing capacity	Readability	Verification value (e)	Minimum load (Min)	Net weight	Dimension weighing platform (W×D×H)
KFP 600V20SNM	600 kg	200 g	200 g	4 kg	96 kg	1000×1000×85 mm
KFP 3000V20LNM	3000 kg	1 kg	1 kg	20 kg	171 kg	1500×1500×85 mm

Model name	Weighing capacity	Readability	Verification value (e)	Minimum load (Min)	Net weight	Dimension weighing platform (W×D×H)
KFP 1500V20NM	1500 kg	500 g	500 g	10 kg	148 kg	1500×1250×85 mm
KFP 1500V20SNM	1500 kg	500 g	500 g	10 kg	96 kg	1000×1000×85 mm
KFP 3000V20NM	3000 kg	1 kg	1 kg	20 kg	149 kg	1500×1250×85 mm
KFP 600V20NM	600 kg	200 g	200 g	4 kg	148 kg	1500×1250×85 mm
KFP 1500V40SM	1500 kg	500 g	500 g	10 kg	97 kg	1000×1000×85 mm
KFP 600V40SM	600 kg	200 g	200 g	4 kg	97 kg	1000×1000×85 mm
KFP 3000V40M	3000 kg	1 kg	1 kg	20 kg	134 kg	1500×1250×85 mm
KFP 1500V40M	1500 kg	500 g	500 g	10 kg	144 kg	1500×1250×85 mm
KFP 6000V20M	6000 kg	2 kg	2 kg	40 kg	208 kg	1500×1500×123 mm
KFP 6V40M	6 kg	500 mg	1 g; 2 g	20 g	6.52 kg	300×240×107 mm
KFP 15V40M	15 kg	1 g	2 g; 5 g	40 g	4.8 kg	300×240×107 mm
KFP 15V40LM	15 kg	1 g	2 g; 5 g	40 g	6.1 kg	400×300×111 mm
KFP 30V40M	30 kg	2 g	5 g; 10 g	100 g	7.7 kg	400×300×111 mm
KFP 30V40LM	30 kg	2 g	5 g; 10 g	100 g	10.2 kg	500×400×120 mm
KFP 60V40M	60 kg	5 g	10 g; 20 g	200 g	9.1 kg	400×300×123 mm
KFP 60V40LM	60 kg	5 g	10 g; 20 g	200 g	10.2 kg	500×400×126 mm
KFP 150V40M	150 kg	10 g	20 g; 50 g	400 g	11.7 kg	500×400×126 mm
KFP 150V40LM	150 kg	10 g	20 g; 50 g	400 g	20 kg	650×500×139 mm
KFP 300V40M	300 kg	20 g	50 g; 100 g	1 kg; 2 kg	20 kg	650×500×139 mm
KFP 30V20LM	15 kg; 30 kg	1 g	5 g; 10 g	20 g	10.53 kg	500×400×127 mm

Model name	Weighing capacity	Readability	Verification value (e)	Minimum load (Min)	Net weight	Dimension weighing platform (W×D×H)
KFP 150V20LM	60 kg; 150 kg	5 g	20 g; 50 g	400 g; 1 kg	18.8 kg	650×500×139 mm
KFP 150V20M	60 kg; 150 kg	5 g	20 g; 50 g	400 g; 1 kg	6.58 kg	500×400×127 mm
KFP 150V30LM-2022e	150 kg	10 g	50 g	1 kg	20.5 kg	650×500×139 mm
KFP 150V30M	150 kg	10 g	50 g	1 kg	9.8 kg	500×400×120 mm
KFP 150V30SM	150 kg	10 g	50 g	1 kg	9.35 kg	400×300×111 mm
KFP 15V20LM	6 kg; 15 kg	500 mg	2 g; 5 g	40 g; 100 g	6.3 kg	400×300×117 mm
KFP 15V20M	6 kg; 15 kg	500 mg	2 g; 5 g	40 g; 100 g	3.8 kg	300×240×109 mm
KFP 15V30M	15 kg	1 g	5 g	100 g	7.9 kg	300×240×107 mm
KFP 300V20M	150 kg; 300 kg	10 g	50 g; 100 g	1 kg; 2 kg	18.8 kg	650×500×139 mm
KFP 300V30M	300 kg	20 g	100 g	2 kg	20.5 kg	650×500×139 mm
KFP 30V20M	15 kg; 30 kg	1 g	5 g; 10 g	20 g	6.3 kg	400×300×117 mm
KFP 30V20SM	15 kg; 30 kg	1 g	5 g; 10 g	100 g; 200 g	3.8 kg	300×240×109 mm
KFP 30V30M	30 kg	2 g	10 g	200 g	7.2 kg	400×300×111 mm
KFP 30V30SM	30 kg	2 g	10 g	200 g	5 kg	300×240×107 mm
KFP 3V20M	3 kg	100 mg	1 g	20 g	3.3 kg	230×230×106 mm
KFP 600V20AM	600 kg	20 g	200 g	4 kg	41.8 kg	800×600×192 mm
KFP 60V20LM	30 kg; 60 kg	2 g	10 g; 20 g	200 g; 400 g	9.8 kg	500×400×127 mm
KFP 60V20M	30 kg; 60 kg	2 g	10 g; 20 g	200 g; 400 g	6.3 kg	400×300×117 mm
KFP 60V30LM-2022e	60 kg	5 g	20 g	400 g	9.8 kg	500×400×120 mm

Model name	Weighing capacity	Readability	Verification value (e)	Minimum load (Min)	Net weight	Dimension weighing platform (W×D×H)
KFP 60V30M	60 kg	5 g	20 g	400 g	7.2 kg	400×300×111 mm
KFP 60V30XLM-2022e	60 kg	5 g	20 g	400 g	20.5 kg	650×500×139 mm
KFP 6V20LM	6 kg	200 mg	1 g; 2 g	20 g; 40 g	3.8 kg	300×240×109 mm
KFP 6V20M	6 kg	200 mg	1 g; 2 g	20 g; 40 g	4.4 kg	230×230×106 mm