# KERN SXC 60K-3L

Interlinked for industry of the future: Stainless steel platform scale with up to four data interfaces and optional alibi memory




| Article codes, product groups & Status information | |
|---|---|
| Model article-code | SXC 60K-3L |
| Model-Serie | SXC |
| Assortment | Scales |
| Product Type | Industrial balance |
| Product group | Platform scales |
| Product usage type | Main article |
| EAN code (Model) | 4045761503243 |
| Predecessor Model | SXC 60K-3L-2.025a |
| Planned start date | 2026-2HJ |
| Customs tariff number | 84238220 |
| CE Label | Yes |
| Country of Origin | CN |

| Technical data - Primary | |
|---|---|
| Weighing capacity | 60 kg |
| Readability | 0,005 kg |
| Minimum piece weight | 50 g |
| Net weight | 20,8 kg |
| Platform size | 500×400 mm |
| Indicator cable length | 3 m |
| Dimension weighing platform (W×D×H) | 500×400×126 mm |

| Technical data - Construction | |
|---|---|
| Dimensions display casing (W×D×H) | 232×150×77,3 mm |
| Material weighing plate | Stainless steel |
| Material Platform construction | Stainless steel |
| Bubble Level | Yes |
| Revolving screw feet | Yes |
| Dimensions of weighing plate (W×D) | 500×400 mm |
| Wall mount | Yes |
| IP protection indicator | IP68 |
| IP protection platform | No IP protection |
| IP protection load cell | IP68, IP69K |

| Technical data - Display | |
|---|---|
| Display height | 48 mm |
| Backlight | Yes |

| Technical data - Power supply | |
|---|---|
| Battery | no battery |
| Mains adapter/adapter included | EURO |
| Charging time | 8 h |
| Input Voltage | 110 V - 240 V AC |
| Operating time (Backlight off) | 48 h |
| Rechargeable battery | Rchrg. battery optional - intern |
| Interfaces | Alibi Speicher (optional, factory);Analog (0 - 10 V) (optional, factory);Analog (4 - 20 mA) (optional, factory);Bluetooth BLE (v4.0) (optional, factory);Ethernet (optional, factory);RS-232 (optional, factory);USB-Device (optional, factory);WLAN (optional, factory) |

# KERN SXC 60K-3L

Interlinked for industry of the future: Stainless steel platform scale with up to four data interfaces and optional alibi memory

| Technical data - Measuring system | |
|---|---|
| Calibration method | Adjusting with external weight |
| Linearity | ± 0,015 kg |
| Recommended adjusting weight | 60 kg (M1) |
| Repeatability | 0,005 kg |
| Resolution | 12.000 |
| Stabilisation time under laboratory conditions | 3 s |
| Warm up time | 30 min |
| Weighing system | Strain gauge |
| Weighing units | %;ffa;g;kg;lb;PCS |
| load cell connection | 6-Leiter |

| Technical data - Environmental conditions | |
|---|---|
| Maximum humidity | 80 % |
| Maximum operating temperature | 40 °C |
| Minimum ambient temperature | -10 °C |
| Minimum humidity | 0 % |

| Technical data - Packing & Shipping | |
|---|---|
| Dimensions packaging (W×D×H) | 930×550×230 mm |
| Gross weight | 26 kg |
| Net weight | 22 kg |
| Shipping method | Parcel service |
| Packaging component - by weight - cardboard | 2 kg |
| Packaging component - by weight - styrofoam | 2 kg |
| Delivery time | 1 d |

| Technical data - Counting data | |
|---|---|
| Counting resolution | 12.000 |
| Mininum piece weight at piece counting (Laboratory) | 5 g |

| Optional Services | |
|---|---|
| DAkkS Calibration | 963-129 |

## Functions

### Standard




### Option




### Factory

