

KERN FK 50

Robust, digital force gauge for tensile and compressive force measurements



Article codes, product groups & Status information

Model article-code	FK 50
Model-Serie	FK
Assortment	Sauter
Product Type	Force measurement
Product group	Digital force-measuring devices (internal sensor)
Product usage type	Main article
EAN code (Model)	4045761139534
Predecessor Model	FK 50-2019a
Planned start date	2009-1HJ
Customs tariff number	90248000
CE Label	Yes

Technical data - Primary

Max. Force	50 N
Readability	0.02 N

Technical data - Display

Display type	LCD
Display digit height	18 mm
Display reverse	Yes

Technical data - Power supply

Power supply	Power supply & battery included
Battery type	Alkali(-Manganese)
Mains adapter/adapter included	CH;EURO;UK;US

Protection Class	No protection class
------------------	---------------------

Technical data - Measuring system

Units	N
Tolerance (% from Max.)	0.5%
Force direction	Compression;tension

Technical data - Functions

Hold-Function	Yes
Peak-Function	Yes

Technical data - Environmental conditions

Maximum operating temperature	30 °C
Minimum storage temperature	60 °C

Technical data - Packing & Shipping

Dimensions packaging (W×D×H)	255×260×80 mm
Gross weight	0.90 kg
Net weight	0.75 kg
Shipping method	Parcel service
UN number	Drycell (UN number Alkaline: none, NiMH: 3496 - Packing instruction #1)
Packaging component - by weight - paper	16 g
Packaging component - by weight - cardboard	584 g
Packaging component - by weight - plastics	4 g

KERN FK 50

Robust, digital force gauge for tensile and compressive force measurements



Packaging component - by weight - styrofoam	148 g
---	-------

Packaging component - by weight - foam	73 g
--	------

Delivery time	1 d
---------------	-----

Optional Services

DAkkS calibration - push/pull	963-361O
-------------------------------	----------

DAkkS calibration - push only	963-261O
-------------------------------	----------

DAkkS calibration - pull only	963-161O
-------------------------------	----------

Functions

Standard



Option

