

KERN FL 5K

Powerful digital force gauge with graphic assisted display for tensile and compressive force measurements with external load cell



Article codes, product groups & Status information

Model article-code	FL 5K
Model-Serie	FL
Assortment	Sauter
Product Type	Force measurement
Product group	Digital force-measuring devices (external sensor)
Product usage type	Main article
EAN code (Model)	4045761215986
Successor Model	FM 5K
Planned start date	2018-2HJ
Customs tariff number	90248000
Model Status	Yes
CE Label	Yes
Country of Origin	TH

Technical data - Primary

Max. Force	5 kN
Readability	2 N

Technical data - Construction

Dimension housing (WxDxH)	175x75x30 mm
Material housing	Aluminium
Mounting thread	threaded hole M12

Technical data - Display

Display type	LCD
--------------	-----

Display digit height	8,5 mm
Display reverse	Yes

Technical data - Power supply

Power supply	Battery & Power supply
Battery type	NiMH
Operating time (Display off)	10 h
Operating time (Display on)	8 h
Mains adapter/adaptor included	CH;EURO
Protection Class	No protection class
Interfaces	Analog (0 +/-2V);RS-232 serienmäßig;USB-Device

Technical data - Measuring system

Units	N
Tolerance (% from Max.)	0,2%
Force direction	Compression;tension

Technical data - Functions

Limit value (Min - Max)	Yes
Interface	Analog (0 +/-2V);RS-232 serienmäßig;USB-Device

Technical data - Environmental conditions

Maximum operating temperature	35 °C
Minimum storage temperature	40 °C

Technical data - Packing & Shipping

KERN FL 5K

Powerful digital force gauge with graphic assisted display for tensile and compressive force measurements with external load cell



Dimensions packaging (W×D×H)	370×325×115 mm
Gross weight	2,4 kg
Net weight	1,4 kg
Shipping method	Parcel service
UN number	Ni-MH (UN 3496, Packing Instruction #0, Not Restricted as per Special Provision A199)
Packaging component - by weight - cardboard	970 g
Delivery time	1 d

Technical data - Counting data

Memory	Yes
Value memory - number of groups	1
Value memory - number of cells (per group)	500

Optional Services

DAkkS calibration - push/pull	963-363
DAkkS calibration - push only	963-263
DAkkS calibration - pull only	963-163

Functions

Standard



Option

