



Discover more details and matching accessories online!

Entry level model into professional counting, counting resolution of 30,000 points, verification optional

Features


- The automatic reference weight optimisation of reference weight gradually improves the average piece weight value
- Programmable using numerical key pad:
  - required reference quantity
  - known reference weight
- Three displays for weight display (verifiable), reference weight, total pieces
- Fill-to-target function: Target count or target weight can be programmed. When the target weight is reached there is an audible and visual signal
- 10 memories for reference weights
- Counting results memory: adds up all individual piece counts, result is shown in total weight and total pieces
- Integrated ESD protection, which makes it ideal for weighing small plastic parts
- Energy management: Backlight turns off after 5 sec
- PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels
- Changes from counting mode to weighing mode at the touch of a key
- Protective working cover included with delivery

Technical data

- Large backlit LCD displays, digit height 18 mm
- Dimensions weighing surface, stainless steel, W×D 300×225 mm
- Overall dimensions W×D×H 300×330×110 mm
- Rechargeable battery pack integrated, as standard, operating time up to 200 h without backlight, charging time approx. 8 h
- Net weight approx. 4,0 kg
- Permissible ambient temperature -10 °C/40 °C

Note: Official verification is mandatory for commercial trade

STANDARD | OPTION | FACTORY



CXB-NM

Model	Weighing capacity [Max]	Readability [d]	Verification value [e]	Minimal load [Min]	Smallest part weight (Normal)	Counting resolution	Options	
							Verification	**Calibr. Certificate**
KERN	kg	g	g	g	g/piece	Points	KERN	DAkkS accr. KERN
CXB 3K0.2	3	0,2	-	-	2	15.000	-	963-127
CXB 6K0.5	6	0,5	-	-	5	12.000	-	963-128
CXB 15K1	15	1	-	-	10	15.000	-	963-128
CXB 30K2	30	2	-	-	20	15.000	-	963-128
Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.								
CXB 3K1NM	3	1	1	20	10	3.000	965-227	963-127
CXB 6K2NM	6	2	2	40	20	3.000	965-228	963-128
CXB 15K5NM	15	5	5	100	50	3.000	965-228	963-128
CXB 30K10NM	30	10	10	200	100	3.000	965-228	963-128