

KERN FH 100

Universal digital force gauge for tensile and compressive force measurements with integrated load cell



Article codes, product groups & Status information

Model article-code	FH 100
Model-Serie	FH-S-INT
Assortment	Sauter
Product Type	Force measurement
Product group	Digital force-measuring devices (internal sensor)
Product usage type	Main article
EAN code (Model)	4045761368477
Predecessor Model	FH 100-2019a; FH 100-2023a
Planned start date	2024-2HJ
Customs tariff number	90248000
CE Label	Yes

Technical data - Primary

Max. Force	100 N
Readability	0.05 N

Technical data - Construction

Dimension housing (W×D×H)	45×25×0 mm
Material housing	Plastic
Mounting thread	External thread M6

Technical data - Display

Display type	LCD
Display reverse	Yes

Technical data - Power supply

Power supply

Battery type	NiMH
--------------	------

Operating time (Display off)	40 h
------------------------------	------

Operating time (Display on)	24 h
-----------------------------	------

Technical data - Measuring system

Units	N
Tolerance (% from Max.)	0.5%
Force direction	Compression;tension

Technical data - Functions

Statistic-Function	Yes
Peak-Function	Yes
Limit value (Min - Max)	Yes
Audible ready signal	Yes
Interface	RS-232 standard;USB-Device

Technical data - Environmental conditions

Maximum operating temperature	40 °C
Minimum storage temperature	40 °C

Technical data - Packing & Shipping

Dimensions packaging (W×D×H)	330×190×95 mm
Gross weight	1.4 kg
Net weight	0.55 kg
Shipping method	Parcel service

KERN FH 100

Universal digital force gauge for tensile and compressive force measurements with integrated load cell



UN number Ni-MH (UN 3496, Packing Instruction #0, Not Restricted as per Special Provision A199)

Packaging component - by weight - cardboard 152 g

Packaging component - by weight - styrofoam 404 g

Delivery time 1 d

Technical data - Counting data

Memory Yes

Value memory - number of groups 1

Value memory - number of cells (per group) 10

Optional Services

DAkkS calibration - push/pull 963-361

DAkkS calibration - push only 963-261

DAkkS calibration - pull only 963-161

Functions

Standard



Option

