

PRODUCT BROCHURE

KERN 326-042

Date: 19.03.2025

ENGLISH



Weight set, F1, 1 g - 200 g, Eco Shape, stainless steel polished, in wooden case

CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

Phone : +49 7433 9933-0
Fax : +49 7433 9933-149
Email : info@kern-sohn.com
Web : www.kern-sohn.com

PRODUCT SHOWCASE



SPECIFICATIONS

Article codes, product groups & Status information

Model article-code	326-042
Model-Serie	326
Assortment	KERN
Product Type	Test weights
Product group	OIML F1 Test weights
Product usage type	Main article
EAN code (Model)	4045761224360
Customs tariff number	84239090

Technical data - Primary

Nominal value	1 g - 200 g
Case wood	313-040-100
Weight set case	in wooden case

Technical data - Construction

Material	stainless steel polished
----------	--------------------------

Is weight set yes

Type of case in wooden case

Technical data - Measuring system

Nominal value	1 g - 200 g
OIML class	F1
OIML conform	yes

Technical data - Packing & Shipping

Dimensions packaging (W×D×H)	152×152×66 mm
Gross weight	0.80 kg
Net weight	0.80 kg
Shipping method	Parcel service
Packaging component - by weight - plastics	0 g
Delivery time	1 d

Optional Services

DAkkS Calibration 962-417

FUNCTIONS

Standard



SERVICES

Model	Description
962-417	DAkkS Calibration KERN 962-417
962-417R	DAkkS Recalibration KERN 962-417R
921-417	Guaranteed Plus-deviation (? +1/3 OIML) KERN 921-417
920-712	Marking (Last digits of serial number) KERN 920-712

SPARE PARTS

Model	Description
313-040-100	Box of Weights KERN 313-040-100
315-242	Tweezers KERN 315-242

RELATED ARTICLES DATA

Model name	Nominal value	Tolerance (OIML)	Case aluminium	Case plastic	Case wood	Weight set case
326-36	5 kg	25 mg	346-060-600	not available	not available	-
326-37	10 kg	50 mg	346-070-600	not available	not available	-
326-38	20 kg	100 mg	346-080-600	not available	not available	-
326-39	50 kg	250 mg	346-090-600	not available	not available	-
326-022	1 g - 50 g	-	-	-	313-020-100	in wooden case
326-024	1 g - 50 g	-	-	313-052-400	-	in plastic case
326-026	1 g - 50 g	-	314-020-600	-	-	in aluminium case
326-032	1 g - 100 g	-	-	-	313-030-100	in wooden case
326-034	1 g - 100 g	-	-	313-052-400	-	in plastic case

Model name	Nominal value	Tolerance (OIML)	Case aluminium	Case plastic	Case wood	Weight set case
326-036	1 g - 100 g	-	314-030-600	-	-	in aluminium case
326-042	1 g - 200 g	-	-	-	313-040-100	in wooden case
326-044	1 g - 200 g	-	-	313-052-400	-	in plastic case
326-046	1 g - 200 g	-	314-040-600	-	-	in aluminium case
326-052	1 g - 500 g	-	-	-	313-050-100	in wooden case
326-054	1 g - 500 g	-	-	313-052-400	-	in plastic case
326-056	1 g - 500 g	-	314-050-600	-	-	in aluminium case
326-062	1 g - 1 kg	-	-	-	313-060-100	in wooden case
326-064	1 g - 1 kg	-	-	313-082-400	-	in plastic case
326-066	1 g - 1 kg	-	314-060-600	-	-	in aluminium case
326-072	1 g - 2 kg	-	-	-	313-070-100	in wooden case
326-074	1 g - 2 kg	-	-	313-082-400	-	in plastic case
326-076	1 g - 2 kg	-	314-070-600	-	-	in aluminium case
326-082	1 g - 5 kg	-	-	-	313-080-100	in wooden case
326-084	1 g - 5 kg	-	-	313-082-400	-	in plastic case
326-086	1 g - 5 kg	-	314-080-600	-	-	in aluminium case
326-092	1 g - 10 kg	-	-	-	313-090-100	in wooden case
326-096	1 g - 10 kg	-	314-090-600	-	-	in aluminium case
326-01	1 g	0,1 mg	317-010-600	347-030-400	317-010-100	-
326-02	2 g	0,12 mg	317-020-600	347-030-400	317-020-100	-
326-03	5 g	0,16 mg	317-030-600	347-030-400	317-030-100	-
326-04	10 g	0,2 mg	317-040-600	347-050-400	317-040-100	-
326-05	20 g	0,25 mg	317-050-600	347-050-400	317-050-100	-
326-06	50 g	0,3 mg	317-060-600	347-070-400	317-060-100	-
326-07	100 g	0,5 mg	317-070-600	347-070-400	317-070-100	-

Model name	Nominal value	Tolerance (OIML)	Case aluminium	Case plastic	Case wood	Weight set case
326-08	200 g	1 mg	317-080-600	347-080-400	317-080-100	-
326-09	500 g	2,5 mg	317-090-600	347-090-400	317-090-100	-
326-11	1 kg	5 mg	317-110-600	347-110-400	317-110-100	-
326-12	2 kg	10 mg	317-120-600	347-120-400	317-120-100	-
326-13	5 kg	25 mg	317-130-600	347-130-400	317-130-100	-
326-14	10 kg	50 mg	317-140-600	347-140-400	317-140-100	-