KERN EOC 300K-2L

Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use



Article codes, product groups & Status information	
Model article-code	EOC 300K-2L
Model-Serie	EOC
Assortment	Scales
Segment	Industrial balance
Product group	Platform scales
Product usage type	Main article
EAN code (Model)	4045761192294
Planned start date	2017-1HJ
Customs tariff number	84238220
CE Label	Yes
Country of Origin	CN

Technical data - Primary	
Weighing capacity	150 kg;300 kg
Readability	0,05 kg;0,1 kg
Minimum piece weight	1 kg
Net weight	18,4 kg
Platform size	600×500 mm
Indicator cable length	3 m
Dimension weighing platform (W×D×H)	600×500×150 mm

Technical data - Construction	
Dimensions display casing (W×D×H)	268×115×80 mm
Material weighing plate	Stainless steel
Material Platform construction	Mild steel
Bubble Level	Yes
Revolving screw feet	Yes
Weighing surface (d)	600×500 mm
Dimensions of weighing plate (W×D)	600×500 mm
Indicator cable length	3 m
Wall mount	Yes
IP protection indicator	No IP protection
IP protection platform	IP65
IP protection load cell	IP65

Technical data - Display	
Display height	25 mm
Backlight	Yes

Technical data - Power supply	
Operating time	100 h
Mains adapter/adapter included	CH;EURO;UK
Charging time	3 h
Input Voltage	100V-240V, 4A
Operating time (Backlight off)	43 h
Rechargeable battery	Rchrg. battery optional - intern
Interfaces	RS-232 standard

Technical data - Measuring system	
Calibration method	Adjusting with external weight

KERN EOC 300K-2L

Robust and high-resolution platform scale with practical Flip/Flop display device for greatest ease of use

Linearity	± 0,15 kg;0,3 kg
Readability	0,05 kg;0,1 kg
Recommended adjusting weight	300 kg (M1)
Repeatability	0,05 kg;0,1 kg
Resolution	3.000, 3.000
Stabilisation time under laboratory conditions	2 s
Tare range	300 kg
Warm up time	10 min
Weighing system	Strain gauge
Weighing units	G;kg;lb;oz;PCS
Linearity (in dots)	3
load cell connection	6-Leiter

Technical data - Environmental conditions

Maximum humidity	80 %
Maximum operating temperature	40 °C
Minimum ambient temperature	-10 °C
Minimum humidity	0 %

Technical data - Packing & Shipping

Dimensions packaging (W×D×H)	998×630×190 mm
Gross weight	26 kg
Net weight	19 kg
Shipping method	Parcel service
Packaging component - by weight - paper	70 g
Packaging component - by weight - cardboard	1,62 g
Packaging component - by weight - plastics	12 g
Packaging component - by weight - foam	475 g
Delivery time	1 d

Technical data - Counting data

Counting resolution	3.000
Mininum piece weight at piece counting (Laboratory)	100 g
Minimum piece weight	100 g

Optional Services

DAkkS Calibration	963-129

Functions

Standard



Option

